

Clivus® Economic Solutions Through Recycling

Clivus New England, Inc.

P.O. Box 127 • North Andover, MA 01845

Tel: 978-794-9400 • Fax: 978-794-9444

E-mail: 123CNE@clivusne.com • www.clivusne.com

Saves water:

Thanks to the foaming action of the Neponol soap used, the Nepon Toilet can be flushed with only 3-ounces of water.

No splashing:

The foam blanket prevents any splashing.

Hygienic:

Neponol foam and flush action prevents "streaking" and keeps the toilet bowl clean at all times.

· Continuous and flush foam:

Intermittent foaming control for continuous foam and push button flush foam with microcomputer.

· Neponol:

An alcohol-type biodegradable mild surface agent displaying superior cleaning, foaming and lubricating effects. One bottle of Neponol is good for 1 month of average use.



Specifications:

Model: 3-ounce foam flush

Weight: 88 pounds including packaging

Power: 120V AC

Power consumption: Normal – approximately 4 watts

Foam flush – approximately 8 watts for 45 seconds

Toilet body material:

Water tank material:

Vitreous ceramic

Vitreous ceramic

Water tank capacity: 9.5 quarts
Toilet seat material: ABS U-shaped

Toilet lid material: ABS

Center line to finished back wall: 22" with 4" PVC waste line only

Finished side wall to center: 15" minimum

Air pump: Diaphragm electromagnetic system

Flush timer: Normal 45 seconds (variable from 30 to 60 seconds)

Foaming elements: Polystyrene fabric

Water supplied required: Provide on either side of toilet

Water supply control: Automatic float

Neponol soap:

An alcohol-type biodegradable mild soap
Minimum toilet plumbing pipe angle: 45 degrees from horizontal or steeper

Color: Ivory ADA compliant: Yes

Warranty: One year Distributed by:

